

## HT11 Series Tower Online UPS

6-20kVA (220V/230V/240V)

HT11 series, ranging from 6kVA to 20kVA, is double conversion online UPS with fully DSP controlled technology. The single phase UPS applies the advanced 3-level technology, achieving efficiency up to 95%. With its compact design of high power density (kW=kVA), HT11 series makes it an ideal choice for computers, telecommunication equipment and sensitive devices.



### Application

IDC(Internet Data Center), network, servers and workstations, office etc

### Features

- High efficiency, up to 95%
- Intelligent charging management, effectively improving the life time of battery
- kVA=kW, Output PF=1
- Smaller size with higher power density
- 3 level of technology, compatible with complicated load
- Parallel up to 2 units
- Battery number can be set on LCD
- 12A charger for option, charging for large capacity batteries

### Specification

MODEL	HT1106XS	HT1106XL	HT1110XS	HT1110XL	HT1115XL	HT1120XL
Capacity	6kVA/6kW	6kVA/6kW	10kVA/10kW	10kVA/10kW	15kVA/15kW	20kVA/20kW
Phase	Single phase in, Single phase out					
Input voltage range	110Vac~288Vac 100% load@ > 176Vac; 90% load@ > 160Vac 80% load@ > 140Vac; 60% load@ > 110Vac					
Input THDi	≤4%@100% load; ≤6%@50% load (linear load)					
Input PF	≥0.99					
Input frequency range	40Hz-70Hz					
Output PF	1					
Output voltage	220V/230V/240V					
Voltage regulation	±1%					
THDu	≤1%(linear); ≤5% (non-linear)				≤1%(linear); ≤3% (non-linear)	
Battery voltage	192Vdc					
Battery type/number	12V, 7Ah*16	External	12V, 9Ah*16	External	External	
System efficiency	Normal mode: 95%					
Noise(1 meter away)	<48dB@<70%load; <58dB@>70%load				<50dB@<70%load; <58dB@>70%load	
Overload capability (Inverter mode)	110%: for 10 min;125%: for 1 min; 150%: for 30 second					
Overload capability (Battery mode)	110%: shut down after 1 min; 130%:shut down after 10 second; >130%: shut down after 200 ms					
Crest factor	3:1					
Display	LED+LCD					
Interface	Standard:RS232 Optional: SNMP, USB, RS485, Dry Contacts, Parallel Kit					
W*D*H (mm)	190*426*705	190*426*336	190*485*705	190*485*336	190*485*480	
Package Weight (kg)	56	14	60	16	33	