

Capacity	20-200KVA					
<b>Main Input</b>						
Input voltage	380V/400V/415V(line to line) 220V/230V /240V(line to neutral)					
Input frequency	50/60Hz					
Power factor	>0.99					
Input voltage window	-40%~+25%,-10%~-40% rated power derating from 100%~50%					
Frequency window	40-70HZ					
<b>Battery</b>						
Battery voltage	±240VDC					
Charger power	20%*Active Power					
Charger voltage precision	1%					
<b>Bypass</b>						
Bypass voltage	380V/400V/415V, line to line 220V/230V/240V, line to neutral					
Bypass voltage window	-20%~+15%, full load					
Bypass overload capability	125%, long time operation					
	125%< load <130%, last for more than 1 hour					
	130%<load<150%,last for more than 6 minutes					
>1000%, last for more than 100ms						
<b>Output</b>						
Output voltage	380V/400V/415V, line to line 220V/230V/240V, line to neutral					
Voltage precision	1% (balance load),1.5% (unbalance load)					
Voltage THD(Total Harmonic Distortion)	THD<1.5%(linear load),THD<7%(nonlinear load)					
Power factor	0.9					
Phase tolerance	120°±0.5° (balance and unbalance load)					
Crest factor	3:1					
Overload capability	105% transfer to bypass after 30 minutes					
	110%, transfer to bypass after 10minutes					
	125%, transfer to bypass after 1 minutes					
	150%, transfer to bypass after 30 seconds					
	>150%, transfer to bypass after 200ms					
<b>System</b>						
System efficiency	Normal mode: 94.5% @60~70% load					
	ECO mode: 98%					
Battery mode efficiency	94.5% @60~70% load					
Display	LCD+LED, Touch screen and keyboard					
IP class	IP20					
Interface (Communication Ports )	RS232,RS485,Dry contacts,SNMP card,EPO,Generator interface					
Installation/Connection	Top or bottom cable connection					
Operation temperature	0~40°C					
Storage temperature	-25°C~70°C					
Relative humidity	0~95% (non-condensing)					
Noise(dB)	<55dB					
Weight(KG)	3-module cabinet	RM060/20	171KG			
	6-module cabinet	RM120/20	277KG			
	10-module cabinet	RM200/20	399KG			
	PM20	20KVA: 22KG				
Dimension(W*D*H)(mm)	3-module cabinet	600*900*1100				
	6-module cabinet	600*900*1600				
	10-module cabinet	600*900*2000				
	Module	440*590*134				

\*Products specifications are subject to change without further notice.